



Revision Number: 006.0

Issue date: 10/25/2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE 567 TB 50ML EN
Product type/use: Adhesive/Sealant
Restriction of Use: None identified
Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

IDH number: 2087067
Item number: 2087067
Region: United States
Contact information:
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

WARNING: MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1

PICTOGRAM(S)**Precautionary Statements**

Prevention: Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.
Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage: Not prescribed
Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
3,3,5 Trimethylcyclohexyl methacrylate	7779-31-9	10 - 30
Ethene, tetrafluoro-, homopolymer	9002-84-0	5 - 10
Ethene, homopolymer	9002-88-4	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Propane-1,2-diol	57-55-6	1 - 5
Cumene hydroperoxide	80-15-9	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If inhaled, immediately remove the affected person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation persists, call a physician.
Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a specialist.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.
Hazardous combustion products:	Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics. Toxic fluorine compounds. Ketones.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Store frost-free.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
3,3,5 Trimethylcyclohexyl methacrylate	None	None	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Ethene, homopolymer	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Paste, Liquid

Color:

Off white

Odor:

Mild

Odor threshold:

Not available.

pH:

Not applicable, Product is non-polar/aprotic.

Vapor pressure:

< 0.30 mbar (20 °C (68°F))

Boiling point/range:

> 150 °C (> 302°F) no method / method unknown

Melting point/ range:

Not applicable, Product is a liquid

IDH number: 2087067

Product name: LOCTITE 567 TB 50ML EN

Specific gravity:	1.15
Vapor density:	> 1 20 °C
Flash point:	> 100 °C (> 212°F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	The product is not flammable.
Evaporation rate:	Not available.
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available.
VOC content:	0.13 % (ASTM D5403)
Viscosity:	300,000 - 800,000 mPa.s
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Hazardous decomposition products:	Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics. Toxic fluorine compounds. Ketones.
Incompatible materials:	Strong oxidizing agents. Strong reducing agents. Free radical initiators. Inert gases. Oxygen scavengers.
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
3,3,5 Trimethylcyclohexyl methacrylate	None	No Records
Ethene, tetrafluoro-, homopolymer	None	No Target Organs
Ethene, homopolymer	None	No Target Organs
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg	Irritant
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
3,3,5 Trimethylcyclohexyl methacrylate	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Ethene, homopolymer	No	No	No
Titanium dioxide	No	Group 2B	No
Silica, amorphous, fumed, crystal-free	No	No	No
Propane-1,2-diol	No	No	No
Cumene hydroperoxide	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
DOT Hazardous Substance(s): alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis.
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: None above reporting de minimis.
CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/25/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.