



Actual

Catalog Number: LT9250T-SC
Product ID: 7TAA115120R0038
UPC Number: 78599108608
Status: A

Liquidtight Conduit Fitting, 90 Degree Bend, Insulated, Trade Size 2-1/2 Inch, Malleable Iron

- Typical applications include motor and control, heating and air conditioning, outdoor lighting and transformer connection
- To positively bond conduits to a box or an enclosure indoors and outdoors
- To protect conductors from mechanical damage due to vibration and movement, and seal out cutting oils, coolants, etc.

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Steel City
Type	Connectors-90 Degree
Special Features	Screw in Ferrule and Split Sealing Ring Makes for a Quick Install While Still Providing a Liquidtight Seal that Meets UL Standards
Application	Typical Applications Include Motor and Control, Heating and Air Conditioning, Outdoor Lighting and Transformer Connection
Standard	UL E23018
Size	2-1/2 Inch
Material	Malleable Iron
Color	Metallic
Insulation	Yes

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	2 1/2 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Material housing	Other
Surface protection	Untreated
Thread length	26.0mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	16.5x7.1x5.6
Weight Uom	8.2 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-001715
--------------------------------	------------

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com