

Weatherproof receptacle covers

Industrial specification grade device covers

Product description

Metal covers for FS/FD boxes

Deluxe weatherproof covers for FS/FD boxes

Features

- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- Diecast copper free aluminum with epoxy finish provides maximum corrosion resistance
- Self-closing spring door assures full protection
- EPDM gasketing material on WLRD1 and WLRS1 provide excellent resistance to ozone, weathering and temperatures from -46°C to 127°C (-50°F to 260°F)

Diecast aluminum receptacle covers



Description

Catalog no.

Duplex receptacle cover, horizontal mounting

□ WLRD1

Single receptacle cover, vertical mounting, 1.38" (34.9mm) face diameter, use with 15A, 20A straight blade and 15A receptacles

□ WLRS1

Single receptacle cover, vertical mounting, 1.56" (39.7mm) face diameter, use with 20A and 30A receptacles

□ WLRS2

Standard weatherproof covers for FS/FD boxes

Features

- UL Listed for wet locations (cover closed) and damp locations (cover open or closed)
- Meets 2014 NEC® 406.9 (A) and 406.9 (B)(2)
- Self-closing spring door assures full protection
- Gasketing material provides excellent resistance to weather
- Duplex covers can be used with any duplex receptacle

Diecast aluminum receptacle covers



Description

Catalog no.

Duplex receptacle cover, vertical mounting

□ AH7879*

Single receptacle cover, vertical mounting, 1.38-1.56" (34.9-39.7mm) face diameter, use with 15A and 20A single straight blade receptacles and 15A, 20A and 30A single receptacles

□ 7420



Single receptacle cover, vertical mounting, 1.38-1.56" (34.9-39.7mm) face diameter, yellow corrosion resistant finish, used with 15A and 20A single straight blade receptacles and 15A, 20A and 30A single receptacles


□ 7420CR

Single receptacle, vertical mounting for 2.12" (53.8mm) face diameter, use with 30A straight blade receptacles


□ 7420A

* Not UL Listed


Note: Cat. no. 7420, 7420CR have inserts for protecting toggle; can be used with most standard length toggle switches.




WLRD1



WLRS1



7420



7420CR

Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-32