



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Stem Caster, model _____. For use with 1"-diameter posts. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. For electronic handling, conductive casters and vibration dampening casters available. Donut bumper included with all stem casters. Swivel casters have a temperature rating of -15°F (-26°C). Note: These stem casters cannot be used with Master Trak® Shelving.



swivel caster with resilient tread



(nickel-plated) caster with polyurethane tread



conductive caster

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Stem Casters

MODELS:

- CSS4-125 CSR5P-* CPSB5PS-* A201008
- CSS5-* CSS5PS-* SCS5-* A201009
- CSB5-* CSB5PS-* SCSB5-* A204795
- CSR5-* CSR5PS-* SCSR5-* A207562
- CSS5P-* CSPB5-300 A201706 A200019
- CSB5P-* CPSS5PS-* A201007 A213261

* See charts for complete model numbers.

Casters with Resilient Tread

type	EAGLEbrite® zinc capacity			stainless steel capacity diameter			wheel face		wheel weight			
	model #	lbs.	kg	model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS4-125	125	56.7	n/a			4"	102	1"	25	1.1	0.5
swivel	CSS5-125	125	56.7	n/a			5"	127	1"	25	2.0	0.9
swivel	CSS5-300	300	136.1	CSS5S-200	200	90.7	5"	127	1 1/4"	32	2.5	1.2
w/brake	CSB5-300	300	136.1	CSB5S-200	200	90.7	5"	127	1 1/4"	32	2.8	1.3
w/step-pedal brake	CSPB5-300	300	136.1	n/a			5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5-300	300	136.1	CSR5S-200	200	90.7	5"	127	1 1/4"	32	3.5	1.6

Casters with Polyurethane Tread

type	EAGLEbrite® nickel-plated		stainless steel		wheel diameter		wheel face		weight	
	model #	capacity lbs. kg	model #	capacity lbs. kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5P-300	300 136.1	CSS5PS-300	300 136.1	5"	127	1 1/4"	32	2.5	1.1
w/brake	CSB5P-300	300 136.1	CSB5PS-300	300 136.1	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5P-300	300 136.1	CSR5PS-300	300 136.1	5"	127	1 1/4"	32	3.5	1.6

Conductive Casters For electronic handling only.

type	EAGLEbrite® zinc capacity		wheel diameter		wheel face		weight	
	model #	lbs. kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5-CC	200 90.7	5"	127	1 1/4"	32	2.5	1.1
w/brake	CSB5-CC	200 90.7	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5-CC	200 90.7	5"	127	1 1/4"	32	3.5	1.6

▼ See back page for optional Channel Frames available for use with rigid casters.

EAGLE GROUP
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • Fax: 302-653-2065
 www.eaglegrp.com

Foodservice Division: Phone 800-441-8440
 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our SpecFAB® Division.
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Certifications / Approvals



EG01.05A Rev. 03/17

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com



Profit from the Eagle Advantage®

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Stem Casters



cart-washable
caster

Cart-Washable Casters

Features stainless steel boot, swivel stem, sealed precision bearings, and polyurethane wheel.

type	stainless steel model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5WPS-300	300	136.1	5"	127	1 1/4"	32	2.0	0.9
brake	CSB5WPS-300	300	136.1	5"	127	1 1/4"	32	2.0	0.9



polymer caster

Polymer Casters with polyurethane tread.

type	EAGLEbrite® zinc model #	type of bearing	capacity		wheel diameter		wheel face		weight	
			lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CPSS5-250	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9
brake	CPSB5-250	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9



vibration dampening
caster

Vibration Dampening Casters

For electronic handling. Where vibration dampening is important, these unique 50 shore A hardness "Softie™" casters reduce vibration transfer for work in process.


Replacement Caster Wheel available. Model #SCW-180.

type	EAGLEbrite® zinc model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	SCSS5-180	180	81.6	5"	127	1 3/8"	35	2.0	0.9
brake	SCSB5-180	180	81.6	5"	127	1 3/8"	35	2.5	1.1
rigid ▼	SCSR5-180	180	81.6	5"	127	1 3/8"	35	2.8	1.3

▼ Optional Channel Frames (below) available for use with rigid casters.

Channel Frames—for Rigid Stem Casters

Please note that shelf width must be known when ordering rigid stem casters in order to ship appropriate channel frame to lock rigid casters.



channel frame

model #	shelf width		weight	
	in.	mm	lbs.	kg
A201706	14"	356	1.5	0.7
A201007	18"	457	2.0	0.9
A201008	21"	533	2.5	1.1
A201009	24"	610	2.8	1.3
A204795	30"	762	3.5	1.6
A207562	36"	914	4.0	1.8



donut bumper
#A200019

Donut Bumpers—for all Stem Casters

description	model #
3 1/2" (89mm) diameter	A200019
5" (127mm) diameter, with swivel center	A213261

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.
©2017 by Eagle Group

Rev. 03/17

Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.