



ICE CHESTS
STANDARD, FULL DEPTH WITH COLD PLATE



JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS
TSF Series
TSF18IC10
TSF24IC10
TSF30IC10
TSF36IC10
TSF42IC10
TSF48IC10



Features

- Patented design conceals cold plate under liner for improved sanitation.
- Dent resistant ABS top ledge
- Stainless steel legs install without tools and have rust-free thermoplastic feet
- New full 24" depth

Perlick® ICE CHESTS
STANDARD, FULL DEPTH WITH COLD PLATE

MODEL NOS.	TSF18IC10	TSF24IC10	TSF30IC10	TSF36IC10	TSF42IC10	TSF48IC10
LENGTH, INCHES (mm)	18" (457)	24 (610)	30 (762)	36 (914)	42 (1067)	48 (1219)
ICE CAPACITY, LBS. (kg)	45 (25)	65 (29.4)	85 (38.6)	105 (47.7)	125 (56.7)	145 (65.8)
SHIP WEIGHT, LBS. (kg)	130 (75.5)	140 (95.5)	150 (68.0)	160 (72.6)	170 (77.1)	180 (81.6)
FRONT & SIDES	Stainless steel, top rim ABS					
BACKSPLASH	Stainless steel 6" high (4" optional) with 1" return at top, mechanically fastened and sealed to ice chest top with steel support brackets					
BACK & BOTTOM	Galvanized steel					
INTERIOR	Stainless steel with 1/4" radius corners, welded and sealed with non-exposed cold plate. Interiors can be divided with freestanding ice dividers					
INSULATION	Foamed-in-place polyurethane					
LEGS	1-5/8" tubular, stainless steel with 1" adjustable thermoplastic foot					
PLUMBING	Drain connection - 1/2" NPS male					
COLD PLATE	Cast aluminum plate concealed under ice chest liner. Cold plate has 2 full-length circuits and 8 half-length circuits. Connections - 5/16" O.D. stainless steel tubing with swagged end to accept standard 1/4" I.D. beverage tubing					
OPERATING SPECIFICATIONS	Each full circuit will deliver four 6 oz. drinks per minute at 40° continuously, or 40 oz. every three minutes in a single draw (flow rate 2 oz./sec, 75° ambient, 75° product)					
ACCESSORIES	Cover (stainless steel, two-piece, removable), Ice Divider, 2-Piece Cover, Bottle Wells, Soda Chase, Condiment Trays					

Note: Covers not included.

