



**BOTTLE COOLERS**  
**BC SERIES**

**Perlick Features**

- Heavy-Duty construction
- 2" foamed-in-place insulation provides energy savings and durability
- Revolutionary insulation that has zero ozone depletion potential and zero global warming potential
- Stainless steel interior standard
- Stainless or black vinyl coated exteriors
- Plug-in installation; no condensate plumbing required
- Quiet running, high efficient, balanced refrigeration system
- 24" front to back dimension matches depth of underbar stainless steel
- Reinforced door mullion will not bend or sag
- Dent resistant heavy gauge doors; locks optional
- Standard models factory set to approximately 38°F; Low temp models set to approximately 30°F
- Bottle opener and cap receiver optional

|           |  |
|-----------|--|
| JOB       |  |
| AREA      |  |
| ITEM NO.  |  |
| MODEL NO. |  |

| MODELS |        |
|--------|--------|
| BC24   | BC60   |
| BC24LT | BC60LT |
| BC36   | BC72   |
| BC36LT | BC72LT |
| BC48   | BC96   |
| BC48LT | BC96LT |



**BC24**  
(shown with optional opener, receiver and casters)



**BC36**  
(shown with optional casters)



**BC72**  
(shown with optional opener, receiver and casters)



# BOTTLE COOLERS

## BC SERIES

| MODEL NO.   | BC24/<br>BC24LT   | BC36/<br>BC36LT | BC48/<br>BC48LT | BC60/<br>BC60LT | BC72/<br>BC72LT | BC96/<br>BC96LT |               |
|---|---|-----------------|-----------------|-----------------|-----------------|-----------------|---------------|
| <b>CABINET DIMENSIONS</b>                               | Length - Inches (mm)  | 24" (610)       | 36" (915)       | 48" (1219)      | 60" (1524)      | 72" (1829)      | 96" (2439)    |
|   | Depth - Inches (mm)   | 24" (610)       | 24" (610)       | 24" (610)       | 24" (610)       | 24" (610)       | 24" (610)     |
|   | Height - Inches (mm)  | 34-1/4" (870)   | 34-1/4" (870)   | 34-1/4" (870)   | 34-1/4" (870)   | 34-1/4" (870)   | 34-1/4" (870) |
| <b>INTERIOR CUBIC FOOT (m<sup>3</sup>)</b>              | 4.0 (.11)   | 7.6 (0.21)      | 12.6 (0.36)     | 16.5 (0.47)     | 20.6 (0.58)     | 28.7 (0.81)     |               |
| <b>CASE CAPACITY (based on 12 oz. long neck bottle)</b> | 5.5   | 9.75            | 17.2            | 21              | 28.3            | 41              |               |
| <b>CASE CAPACITY (based on 12 oz. cans)</b>             | 7   | 16              | 25              | 30              | 36              | 58              |               |
| <b>CONDENSER UNIT H.P.</b>                              | 1/5   | 1/5             | 1/4             | 1/3             | 1/3             | 1/3             |               |
| <b>RUNNING LOAD - AMPS</b>                              | 3.2   | 3.0             | 5.2             | 7.0             | 6.9             | 7.6             |               |
| <b>SHIP WT. Lbs. (kg)</b>                               | 190 (86)  | 245 (111)       | 300 (136)       | 353 (160)       | 405 (184)       | 515 (235)       |               |
| <b>INTERIOR</b>   | All models have stainless steel walls and floor   |                 |                 |                 |                 |                 |               |
| <b>EXTERIOR</b>   | Choice of black, stainless steel and all stainless. All tops are stainless steel.<br><b>Black Option:</b> Front and ends are black vinyl coated steel, back and bottom are galvanized.<br><b>Stainless Steel Option:</b> Front and ends are stainless steel, back and bottom are galvanized.<br><b>All Stainless Option:</b> Front, ends, back and bottom are stainless steel.  |                 |                 |                 |                 |                 |               |
| <b>TEMPERATURE</b>                                      | Factory set at approximately 38°F for Standard models, 30°F for Low-temp models   |                 |                 |                 |                 |                 |               |
| <b>DOORS (SLIDING)</b>                                  | Stainless steel top and bottom pans. Die cast handle. Optional locks.   |                 |                 |                 |                 |                 |               |
| <b>REFRIGERATION</b>                                    | R134a capillary tube/type with hermetic condensing unit. Pulls out for service and cleaning. Low-temp models have automatic defrost   |                 |                 |                 |                 |                 |               |
| <b>ELECTRICAL</b>                                       | 115V, 60Hz., 1 Phase AC. Furnished with 6 foot NEMA 5-15P rubber plug-in cord (115V model only). Also available in 230V, 50Hz., 1 Phase AC. Carries CE marking conformity, applies to models BC24-230, BC36-230 & BC48-230.   |                 |                 |                 |                 |                 |               |
| <b>PLUMBING</b>   | None required. Condensate evaporates automatically.   |                 |                 |                 |                 |                 |               |
| <b>INSULATION</b>                                       | 2" Foamed-in-place polyurethane insulation  |                 |                 |                 |                 |                 |               |
| <b>VENTILATION</b>                                      | BC24 model is front vented, all other models require 2" clearance from wall either on left end or back of cabinet for proper air flow.  |                 |                 |                 |                 |                 |               |
| <b>OPTIONAL ACCESSORIES</b>                             | <ul style="list-style-type: none"> <li style="width: 33%;">• Floor Racks</li> <li style="width: 33%;">• Casters</li> <li style="width: 33%;">• Bottle opener and receiver</li> <li style="width: 33%;">• Roller Basket Shelving</li> <li style="width: 33%;">• Bin Dividers</li> <li style="width: 33%;">• Speed Rails</li> <li style="width: 33%;">• Wine Temperature (specify red or white)</li> <li style="width: 33%;">• Interior Light</li> <li style="width: 33%;">• Interior light kit (installed)</li> <li style="width: 33%;">• Adjustable Legs</li> <li style="width: 33%;">• Door Locks</li> </ul> |                 |                 |                 |                 |                 |               |

\* NOTE: This equipment is intended for the storage and display of non-potentially-hazardous bottled or canner products only.

