

EXTRA WIDE REACH-IN
DUAL TEMPERATURE

VICTORY ULTRASPEC™
FEATURING: **SecureTemp™ 1.0**

Full Door	Half Door
HRS-2D-S1-EW	HRS-1D-S1-EW-HD HRS-2D-S1-EW-HD
HRSA-2D-S1-EW HRSA-2D-S1-EW	HRSA-1D-S1-EW-HD HRSA-2D-S1-EW-HD

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- Touch Point™ Electronic Control System
- LED Lighting with Proximity Door Switch, Activates Interior Lighting
- Expansion Valve Technology
- 20 Gauge, Stainless Steel Doors
- Dual Speed, Energy Efficient, EC Fan Motors
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Stainless Steel Breakers
- High Performance, Balanced, Top-Mounted Refrigeration
- Plasticized Evaporator Fin Coils
- Non-Electric Condensate Evaporator
- Foamed-in-Place Polyurethane Insulation
- Insulated Partition Wall Separates Compartments
- Heavy Duty Cylinder Locks
- Self-Closing Doors with 120° Hold Open Feature
- Cam-Lift Hinges, Guaranteed for Life
- Ergonomically Correct Door Handles, Guaranteed for Life
- S, SA Series have 6" High, Adjustable Stainless Steel Legs
- Hinged Front Shroud Makes Condenser Cleaning Easier
- One Piece, Snap-In Magnetic Door Gasket(s)
- Anti-Condensate Door Perimeter Heaters
- Stainless Steel Interior Door Liner
- Energy Saving Thermal Breaker Caps, Guaranteed for Life
- Two (2) Epoxy Coated Wire Shelves per 1/2 Section
- Three (3) Epoxy Coated Wire Shelves per Cabinet Section (2-section models)
- One (1) Epoxy Wire Shelf per Cabinet Section (1-Section Models)
- Cord and Plug (see electrical data for details)



HRS-1D-S1-EW-HD

OPTIONS & ACCESSORIES

- Correctional Facilities Options
- Stainless Steel Shelves
- Stainless Steel Case Back and Shroud
- 6" Overall Height Casters (set of 4)
- Exterior Laminate Décor
- Adjustable Tray and Pan Slides
- Optional Voltages



3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

CABINET CONSTRUCTION

The cabinet front and doors are constructed of heavy gauge, polished stainless steel to maintain an attractive appearance after years of heavy use. Polyurethane foam insulation throughout ensures the ultimate in energy efficiency. The front shroud lifts up for easy access when cleaning the condenser unit.

DOOR CONSTRUCTION

The doors are heavy gauge, polished stainless steel with a stainless steel interior liner. Each door is provided with a cylinder lock and ergonomically correct vertical handle. The door hinges are self-closing and have a hold-open feature at 120° which facilitates product loading. Proximity switches energize the recessed interior incandescent lighting when the door is opened. Humidity control wires around the door jamb prevent condensation from forming on the front of the cabinet in high humidity environments. The wires are concealed by a high impact, non-conducting thermal breaker cap.

REFRIGERATION SYSTEM

All components of the high efficiency, air-cooled, self-contained refrigeration system are mounted on top of the cabinet out of the food storage zone providing greater usable storage space. Environmentally friendly R-134a refrigerant is efficiently metered by a capillary system providing a constant, safe operating temperature and quick "recovery" under the most demanding conditions. The hermetically sealed system is designed to operate at 38° F. The cooling coil has plasticized fin coils to resist food acids and dual-speed EC fan motor(s) for greater cooling capacity and efficiency. All condensate water is disposed of automatically by the condensate vaporizer on the single section and disposed of automatically with the non-electric hot gas disposal system on the two section model.

HEATING SYSTEM

The safety shielded, "strip type" heaters located at the bottom of the cabinet interior are precisely controlled by the V-TEMP™ electronic control with a temperature range from 80° F to 180° F. An externally mounted blower system ensures even temperatures throughout the cabinet interior. A built-in, adjustable humidity control vent allows the operator to maintain a moist or more dry environment.

INTERIOR STORAGE ARRANGEMENTS

Shelves are adjustable in one inch increments. A wide door opening allows for the use of a variety of optional pan slide configurations including 18" x 26" and 12" x 20" pans.

V-TEMP™ CONTROL SYSTEM

The easy to use V-TEMP™ Control is standard. This durable, water resistant microprocessor monitors and controls the entire temperature maintenance process. It includes an ON/OFF switch, manual defrost, interior light switch, LED temperature indicator in °C or °F, a HI/LO audio/visual temperature alarm, power supply interruption, door ajar and "clean condenser" alarms. A manager's "lock-out" feature is provided to safeguard predetermined control settings. A HAACP Event Indicator/Memory feature announces and records up to nine (9) alarm events. Unique to the V-TEMP™ are two standard modes of operation:

SUPERCOOL - Provides a lower "set-point" refrigeration condition for a set period of time when food has just been loaded into the refrigerator and needs to be quickly brought back down to a safe temperature.

ENERGY SAVING - The cabinet automatically reverts to the energy saving mode when there are no door openings for four hours.

CHARACTERISTICS	1 Section	2 Section
Net Capacity	10.1	23.8
Width, Overall (in.)	31 1/4	58 3/8
Depth, Overall (inc. Handles)	35	35
Depth, Door(s) Open 90°	58 1/4	58 1/4
Clear Door Width (in.)	22 1/2	22 1/2
Clear Half-Door Height (in.)	N/A	25 3/8
Clear Full-Door Height (in.)	55 1/4	55 1/4
Height Overall (inc. 6" legs)	84 1/4	84 1/4
No. Full Doors	2H	2F, 4H
No. of Shelves	2	6

ELECTRICAL DATA

Warmer Cabinet Voltage (6-20P plug)	208-240/60/1	208-240/60/1
Heater Watts per Section (@240V)	1,000	1,500
Condensing Unit Voltage, Refrigerator	115/60/1	115/60/1
NEMA Plug, Refrigerator	5-15P	5-15P
Total Amperes, Refrigerator	11.6	9.0

NOTE: Units include TWO (2) Plugs. One 5-15P for Refrigerator and one 6-20P cord for warmer.

REFRIGERATION DATA

Condensing Unit Size, Refrigerator	1/3 HP	1/3 HP
Refrigerant, Refrigerator	R-134A	R-134A

CRATED DIMENSIONS	Height	Width	Depth	Cu. Ft.	Lbs.
One Section	83	36	44	7608	480
Two Section	83	63	44	133.15	660

Note: In order to provide peak operating performance the cabinet must have a 2 inch all around clearance and 12 inches above the top of the condensing unit. This ensures an adequate air supply and space for routine maintenance and/or service if required.

* Remote units use R-404A refrigerant standard and come with 6" legs

