



VITALink® CIC, 2-Hour Fire Rated, UL Listed LSZH FPLR, 105°C-300 Volt-UL Listed, Nonshielded



Product Construction

Conductor:

- Solid copper specially engineered to minimize embrittlement due to fire exposure

Insulation:

- Proprietary Low Smoke, Zero Halogen Thermoset Fire-Roc™ Layer

Cable Core:

- Color Coded Conductors: Black and Red

Drain Wire:

- Stranded bare copper

Jacket

- Red Low Smoke, Zero Halogen Polyolefin

Applications

- Manufacturing, Commercial and Industrial locations
- Colleges, High-rise Buildings, Hotels, Airports and Stadiums
- Health Care Facilities
- Tunnels and Subways for Emergency Communications

Standards

- NEC type FPLR for use in Electrical Circuit Integrity System FHIT.40A
- 2-hour fire rating per UL 2196

Additional Information

- VITALink® CI Installation Guide
- UL FHIT 40 Conduit Fill

COLOR CODE CHART	
Cond. #	Color
1	Black, Red & Numbered
2	Black, Red & Numbered

Part #	AWG	Conductors	Lbs./M'
HVC141602	16	2	54
HVC141402	14	2	65
HVC141202	12	2	92

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.