




Multi-conductor-80°C, Unshielded-300 Volt, PVC Insulation-PVC Jacket



Product Construction

Conductor:

- Tinned copper

Insulation:

- PVC Insulated with cabled conductors

Jacket:

- Gray PVC

Applications

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

Standards

- Voltage: UL 300 Volt

COLOR CODE CHART			
Cond.#	Color	Cond.#	Color
1	Black	16	Blue/Black Stripe
2	Red	17	Orange/Black Stripe
3	White	18	Yellow/Black Stripe
4	Green	19	Purple/Black Stripe
5	Brown	20	Gray/Black Stripe
6	Blue	21	Pink/Black Stripe
7	Orange	22	Tan/Black Stripe
8	Yellow	23	Black/White Stripe
9	Purple	24	Red/White Stripe
10	Gray	25	Green/White Stripe
11	Pink	26	Blue/White Stripe
12	Tan	27	Brown/White Stripe
13	Red/Black Stripe	28	Orange/White Stripe
14	White/Black Stripe	29	Yellow/White Stripe
15	Green/Black Stripe	30	Purple/White Stripe

Instrumentation Cable



Part #	AWG	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nom. O.D.	Lbs./M'
D92202	22	2	7x30 TC	.015"	.025"	.170"	8
D92203	22	3	7x30 TC	.010"	.032"	.172"	18
D92204	22	4	7x30 TC	.010"	.032"	.186"	23
D92205	22	5	7x30 TC	.010"	.032"	.194"	26
D92206	22	6	7x30 TC	.010"	.032"	.202"	29.2
D92207	22	7	7x30 TC	.010"	.032"	.214"	33
D92208	22	8	7x30 TC	.010"	.032"	.229"	36.9
D92209	22	9	7x30 TC	.010"	.032"	.244"	42
D92210	22	10	7x30 TC	.010"	.032"	.264"	45
D92212	22	12	7x30 TC	.010"	.032"	.272"	52
D92215	22	15	7x30 TC	.010"	.040"	.315"	72
D92220	22	20	7x30 TC	.010"	.040"	.345"	87
D92225	22	25	7x30 TC	.010"	.040"	.387"	109
D92230	22	30	7x30 TC	.010"	.040"	.400"	124
D92240	22	40	7x30 TC	.010"	.040"	.455"	161
D92250	22	50	7x30 TC	.010"	.045"	.500"	206

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances. *Ring Band Striping