



Continuously Corrugated Welded Cable - CCW® XLPE Insulation - PVC Jacket, 90°C - 600 Volt - UL Type MC -HL



Product Construction

Conductor:

- Bare annealed copper per ASTM B-3
- Compressed Class B stranding per ASTM B8

Insulation:

- Cross-linked Polyethylene (XLPE) type XHHW-2 per UL 44

Shield:

- Class B stranded copper per ASTM B3 and B8
- Cross-linked polyethylene (XLPE) insulation, green
- Sized in accordance with NEC Table 250.122

Aarmor:

- Impervious, continuously welded and corrugated aluminum alloy sheath per UL 1569 and UL 2225
- Meets grounding requirements of NEC Article 250

Jacket:

- Black Polyvinyl Chloride (PVC), sunlight and oil resistant, per UL 1569, 90°C temperature rating

Applications

- Designed for use on power or control circuits
- Can be installed in cable tray, wire ways, racks, or buried directly
- Suitable for exposure to hazardous locations, Type MC-HL for Classes I, II, and III Division 1 and 2

Standards

- UL 44, XHHW-2
- UL 1569 Type MC and UL 2225 Type MC-HL
- UL 1309 Marine Shipboard
- UL 1581
- IEEE 1202 available upon request

Armored Cable



Part #	AWG	Conductors	Ground AWG	Nominal O.D. Over Armor	Nom. O.D. Overall	Lbs./M'
X11403	14	3	14	.530"	.640"	203
X11404	14	4	14	.580"	.690"	230
X11405	14	5	14	.600"	.710"	245
X11406	14	6	14	.620"	.730"	278
X11408	14	8	14	.710"	.820"	329
X11409	14	9	14	.740"	.855"	371
X11411	14	11	14	.800"	.910"	404
X11418	14	18	14	.930"	1.04"	556
X11419	14	19	14	.921"	1.028"	572
X11436	14	36	14	1.24"	1.35"	968
X11437	14	37	14	1.22"	1.32"	1030
X11202	12	2	12	.530"	.640"	200
X11203	12	3	12	.580"	.690"	248
X11204	12	4	12	.670"	.780"	295
X11205	12	5	12	.670"	.780"	330
X11206	12	6	12	.670"	.780"	348
X12207	12	7	12	.710"	.820"	408
X12208	12	8	12	.800"	.910"	431
X11211	12	11	12	.890"	1.00"	519
X11212	12	12	12	.885"	.995"	584
X11218	12	18	12	1.02"	1.13"	739
X11236	12	36	10	1.37"	1.48"	1302
X11002	10	2	10	.580"	.690"	253
X11003	10	3	10	.620"	.730"	312
X11004	10	4	10	.670"	.780"	348
X11006	10	6	10	.750"	.860"	451
X11008	10	8	10	.890"	1.00"	568
X11011	10	11	10	.970"	1.08"	704

*Fittings are available for these products.

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager.

General Cable CCW® is a registered trademark of General Cable.

Armored Cable



COLOR CODE CHART	
Cond. #	Color
1	Black
2	Red
3	Blue
4	Orange
5	Yellow
6	Brown
7	Red/Black Stripe
8	Blue/Black Stripe
9	Orange/Black Stripe
10	Yellow/Black Stripe
11	Brown/Black Stripe
12	Black/Red Stripe
13	Blue/ Red Stripe
14	Orange/Red Stripe
15	Yellow/Red Stripe
16	Brown/Red Stripe
17	Black/Blue Stripe
18	Red/Blue Stripe
19	Orange/Blue Stripe
20	Yellow/Blue Stripe
21	Brown/Blue Stripe
22	Black/Orange Stripe
23	Red/Orange Stripe
24	Blue/Orange Stripe
25	Yellow/Orange Stripe
26	Brown/Orange Stripe
27	Black/Yellow Stripe
28	Red/Yellow Stripe
29	Blue/Yellow Stripe
30	Orange/Yellow Stripe
31	Brown/Yellow Stripe
32	Black/Brown Stripe
33	Red/Brown Stripe
34	Blue/Brown Stripe
35	Orange/Brown Stripe
36	Yellow/Brown Stripe
37	Black