

NPA1-2-0500-BK

NPA1-2-0500 is a removable foam tape made to remove cleanly from most hard non-delaminating surfaces even after extended periods of time. NPA1-2-0500 has a permanent adhesive on one side and a removable adhesive on the other side.

Product Information

Product Information	Description	
Foam:	Cross-linked Polyethylene	Thickness (inch): .063
Adhesive:	Permanent Rubber Based DRP75 Removable Rubber Based DRP125	
Release Liner:	Silicone Coated Paper	
Application Temperature (°F):	65 to 100	
Service Temperature (°F):	-20 to 150	

Foam

Typical Properties

Test Method

Density (lb/ft. ³):		2.7-3.3		ASTM D 3575
Compression Deflection (psi):	25%	3.9 min		ASTM D3575
Compression Set (%):	50%	27 max		ASTM D3575
Tensile Strength (psi):	MD	72 min		ASTM D3575
Elongation (% to break):	MD	120 min		ASTM D3575
Tear Resistance (lb/in):	MD	11 min		ASTM D3575

Adhesive*

Typical Properties

Test Method

		<u>DRP75</u>	<u>DRP125</u>	
180° Peel Adhesion (lb/in):		8.0 min	2.5 min	PSTC-101
Shear Resistance (hrs):				
1in ² , 72°F	10 lb load:	72.0 min	100.0 min	PSTC-107
Quick Stick (lb/in):		9.0 min	2.0 min	PSTC-5

MD = Machine Direction CD = Cross Direction

* Tests are performed on 2 mil PET.