

Cold shrink Kit for 1/2 in through 3/8 in cable to 1/2 in through 3/8 in cable

Product Classification

Product Type Cold shrink kit

Dimensions

 Nominal Size
 1/2 in | 3/8 in

 Cable Diameter for Seal, maximum
 21.34 mm | 0.84 in

 Cable Diameter for Seal, minimum
 7.37 mm | 0.29 in

 Inner Diameter
 53.09 mm | 2.09 in

 Length
 202.95 mm | 7.99 in

General Specifications

Application Provides additional moisture seal for cable connections

Applications per KitOne 1/2 in–3/8 in to 1/2 in–3/8 in

Color Black

Includes One EPDM rubber tube | One sealing foam strip

Material Type EPDM rubber

Ordering Note CommScope® non-standard product

Package Quantity 1

Mechanical Specifications

UV Resistance Test MethodUV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp

UV Resistance, minimum with no degradation =1000 hours

Weather Resistance Test Method 04AS00-03.6.0 | MIL-STD-1344A, Method 1002

Packed Dimensions

 Height
 30.0 cm | 11.8 in

 Length
 7.6 cm | 3.0 in

 Shipping Weight
 0.14 kg | 0.30 lb

 Width
 7.6 cm | 3.0 in

Regulatory Compliance/Certifications

Agency Classification

page 1 of 2 June 11, 2019



245173

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system



page 2 of 2 June 11, 2019

