



Universal Grounding Kit for 1/4 in through 5/8 in cables

- c

Product Classification

Product Type Grounding kit

Dimensions

Nominal Size	1/2 in 1/4 in 3/8 in 5/8 in
Bonding Conductor Length	609.6 mm 24 in
Cable Jacketing Removal Length, maximum	59.1 mm 2.3 in
Cable Jacketing Removal Length, minimum	55.9 mm 2.2 in
Compatible Diameter, maximum	15.240 mm 0.600 in
Compatible Diameter, minimum	2.540 mm 0.100 in

Electrical Specifications

Current Handling	Tested to withstand 30,000 amps peak current surge
Current Handling Test Method	MIL-STD-1757
Grounding, Bonding and Shielding Test Method	MIL-STD-188-124A
Lightning Protection Test Method	IEC 1024-1

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Weatherproofing Method	Butyl and electric tape

General Specifications

Grounding Kit Type	Universal Grounding Kits
Cable Type	Corrugated Smoothwall
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in Mexico, Central America, and South America
Color	Black
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	10 gauge
Bonding Conductor Jacketing Material	PVC
Grounding Strap Material	Tinned copper

GK-SUNV

Includes	Grounding kit Hardware Lug One roll of 2 in PVC tape One roll of 24 in butyl rubber tape
Lug Attachment	Factory attached
Lug Type	One-hole lug
Package Quantity	1
Rivet Material	Copper

Mechanical Specifications

Blowing Rain Test Method	MIL-STD-810, Method 506
Corrosion Test Method	MIL-STD-1344, Method 1001
Freezing Rain/Icing Test Method	MIL-STD-810, Method 521
Humidity Test Method	MIL-STD-1344, Method 1002
Immersion Test Method	IEC 60529:2001, IP68
Thread Size	M8
UV Resistance Test Method	MIL-STD-810, Method 505
Vibration Test Method	MIL-STD-202, Method 214

Packed Dimensions

Height	152.4 mm 6.0 in
Length	57.2 mm 2.3 in
Shipping Weight	0.28 kg 0.62 lb
Width	76.2 mm 3.0 in

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



Included Products

- 9905-71 — Black 2 in PVC Tape, 20 ft
- 42615-10 — Butyl Rubber Tape, 24 in

* Footnotes

Grounding, Bonding and Shielding Test Method	Military Standard for Grounding, Bonding, and Shielding: Bond Resistance Requirement of a Maximum dc resistance of 0.001 ohm
---	--

Lightning Protection Test Method

Protection Against Lightning Electromagnetic Impulse, Table 1—Protection Level III–IV, 1995-02