



The NLOS series omnidirectional antenna system offered by Laird Technologies are constructed of UV stabilized fiberglass and stainless steel for long service life. Mounting is easy with a dual u-bolt mounting system. The antennas are vertically polarized and are DC grounded for lightning protection. The 6 dBi and 8 dBi come standard with 18 inch pigtailed terminated in an N female connector. The 5 dBi and 11 dBi come standard with an integrated N Female connector. The 11 dBi is available with 1° electrical downtilt which provides null fill and improved close-in coverage.

FEATURES AND BENEFITS

- 900 MHz omnidirectional antenna
- Available in 5, 6, 8 and 11 dBi gain models
- 1° electrical downtilt available on the 11 dBi model
- Mounting hardware included
- UV stabilized fiberglass / stainless steel construction
- 18 in pigtail with type N female connector standard (6 dBi and 8 dBi models only)


ELECTRICAL SPECIFICATIONS	OD9-5	OD9-6	OD9-8	OD9-11	OD9-11D1
VSWR	1.5:1	1.5:1	1.5:1	1.5:1	1.5:1
Impedance (Ohms)	50	50	50	50	50
Input Power (W)	100	100	100	100	100
Outer diameter mm (Inch)	25-51 (1-2)	25-51 (1-2)	25-51 (1-2)	25-51 (1-2)	25-51 (1-2)
Operating temperature (°C)	-45 to 70	-45 to 70	-45 to 70	-45 to 70	-45 to 70
Rated wind velocity mph (m/s)	125 (56)	125 (56)	125 (56)	125 (56)	125 (56)
Gain (dBi)	5	6	8	11	11
VSWR 1.5:1 bandwidth (MHz)	890-950	865-945	865-945	860-960	860-960
VSWR 2.0:1 bandwidth (MHz)		860-960	860-960		
Vertical 3dB beamwidth (°)	36	16	10	7	7
Electrical downtilt	0	0	0	0	1

MECHANICAL SPECIFICATIONS	OD9-5	OD9-6	OD9-8	OD9-11	OD9-11D1
Dimensions – D x H – mm (inches)	38 x 610 (1.5 x 25.19)	38 x 1700 (1.5 x 66.93)	38 x 2600 (1.5 x 102.36)	38 x 3400 (1.5 x 133.86)	38 x 3400 (1.5 x 133.86)
Radome Material	UV Stabilized Fiberglass				


CONFIGURATION

PART NUMBER	DESCRIPTION	CABLE LENGTH	CONNECTOR
OD9-5	5 dBi Slimline NLOS Series 900 MHz Omni Antenna	N/A	N-Female bulkhead connector
OD9-6	6 dBi NLOS Series 900 MHz Omni Antenna	45.72 cm (18 in.)	N-Female connector
OD9-8	8 dBi NLOS Series 900 MHz Omni Antenna	45.72 cm (18 in.)	N-Female connector
OD9-11	11 dBi NLOS series 900 MHz Omni Antenna	N/A	N-Female connector
OD9-11D1	11 dBi 1° elec downtilt NLOS series 900 MHz omni antenna	N/A	N-Female connector


RADIATION PATTERNS




OD9-5



OD9-6



OD9-8



OD9-11D1

Americas: +1.847.839.6925
 IAS-AmericasSales@lairdtech.com
Europe: +44.1628.858941
 IAS-EUSales@lairdtech.com
Asia: IAS-AsiaSales@lairdtech.com
Middle East and Africa:
 +44.1628.858941
 IAS-MEASales@lairdtech.com
<https://connectivity.lairdtech.com/>



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

