

4.3/10 Low PIM Adapter Series

4.3/10 to 7/16 or N



Connector Type	See part #s below
Frequency Range	DC-7.5GHz
Impedance	50 Ω
Outer Material	Tri-Metal & Silver, RoHS Compliant
Inner Material	Silver
PIM	~ -165dBc for 4.3/10 to 7/16 / ~ -155 dBc for N type
VSWR	≤ 1.10(DC-3G)
Durability	500 Cycles
Pluggable Force	≥ 0.56N
Operating Temp.	-40°F- +185°F

PET-TR-43F43F	Adapter, (4.3/10) Female to (4.3/10) Female, low PIM
PET-TR-43FDF	Adapter, (4.3/10) Female to (7/16) DIN Female, low PIM
PET-TR-43FDM	Adapter, (4.3/10) Female to (7/16) DIN Male, low PIM
PET-TR-43FNF	Adapter, (4.3/10) Female to N Female, low PIM
PET-TR-43FNM	Adapter, (4.3/10) Female to N Male, low PIM
PET-TR-43M43M	Adapter, (4.3/10) Male to (4.3/10) Male, low PIM
PET-TR-43MDF	Adapter, (4.3/10) Male to (7/16) DIN Female, low PIM
PET-TR-43MNF	Adapter, (4.3/10) Male to N Female, low PIM