

# L4A-DMDM-6-P

---



LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male, 6 ft.

## Product Classification

**Product Series** LDF4-50A  
**Product Type** SureFlex® Premium, static PIM

## General Specifications

**Body Style, Connector A** Straight  
**Body Style, Connector B** Straight  
**Interface, Connector A** 7-16 DIN Male  
**Interface, Connector B** 7-16 DIN Male  
**Length** 1.829 m | 6.000 ft  
**Nominal Size** 1/2 in  
**Specification Sheet Revision Level** B

## Electrical Specifications


**3rd Order IMD Static** -159.00 dBc | -116.00 dBm  
**3rd Order IMD Static Test Method** Two +43 dBm carriers  
**DTF, Connector A** -34.00 dB  
**DTF, Connector B** -34.00 dB

## Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition

## Jumper Assembly Sample Label

# L4A-DMDM-6-P



## Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.06	30.00
1700–2200 MHz	1.06	30.00
2200–2700 MHz	1.11	26.00

## Regulatory Compliance/Certifications

### Agency

RoHS 2011/65/EU  
ISO 9001:2015  
China RoHS SJ/T 11364-2014

### Classification

Compliant by Exemption  
Designed, manufactured and/or distributed under this quality management system  
Above Maximum Concentration Value (MCV)



## Included Products

LDF4-50A — LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket (Halogen free jacketing non-fire-retardant)