



1/4" Hiflex - Plenum Rated

FLAME RETARDANT

Cable type : **5042-PL**

Reference : **EC1-50-HF-PL**

Cable with UV resistant, low smoke
flame retardant jacket according to UL-910 / NFPA 262
CATVP rated (Plenum)

CHARACTERISTICS

Construction

• Inner conductor	
Material	copper clad aluminium wire
Diameter (mm) (in)	1.9 (0.07)
• Dielectric	
Material	gas-injected cellular polyethylene
Diameter (mm) (in)	4.6 (0.18)
• Outer conductor	
Material	corrugated copper tube
Diameter (mm) (in)	6.4 (0.25)
• Outer sheath	
Thickness (mm) (in)	0.55 (0.02)
Diameter (mm) (in)	7.5 (0.3)

Mechanical characteristics

• Minimum bending radius	
a) single bending (cm) (in)	2.5 (1.0)
b) 15 repeated bends (cm) (in)	2.5 (1.0)
• Maximum pulling strength (daN) (lb)	30 (67)
• Recommended temperature range	
- Storage	-15 to +85 °C (+5 to +185 °F)
- Installation	-15 to +60 °C (+5 to +140 °F)
- Operation	-15 to +85 °C (+5 to +185 °F)
• Max. length per hoisting grip (m) (ft)	70 (230)
• Maximum hanger spacing (m) (ft)	-
• Flat plate crush res. (kg/mm) (lb/in)	1.8 (104)
• Bending moment (Nm) (lb-ft)	1.1 (0.8)
• Approximate weight (kg/m) (lb/ft)	91 (0.061)

Electrical characteristics

• Characteristic impedance (Ω)	50 ± 1,5
• Nominal capacity (pF/m) (pF/ft)	80.0 (24.4)
• Relative propagation velocity (%)	82
• Inductance ($\mu H/m$) ($\mu H/ft$)	0.203 (0.062)
• DC-resistance at 20°C (68°F)	
- inner conductor (Ω/km) ($\Omega/1000ft$)	9.2 (2.80)
- outer conductor (Ω/km) ($\Omega/1000ft$)	4.4 (1.34)
• RF peak voltage (kV)	0.6
• RF peak power (kW)	3.6
• Cut-off-frequency (GHz)	22.0
• Insulation resistance (M Ω .km)	>> 5000
• Attenuation^[1] and power rating	

Frequency (MHz)	Attenuation at 20°C (68° F) ^[2]		Mean power rating ^[3] (kW)
	(dB/100m)	(dB/100ft)	
10	1.76	0.537	3.9
20	2.49	0.759	2.8
30	3.06	0.933	2.26
80	5.03	1.53	1.37
100	5.63	1.72	1.23
150	6.93	2.11	1.00
200	8.03	2.45	0.86
300	9.89	3.02	0.70
400	11.5	3.50	0.60
450	12.2	3.72	0.57
500	12.9	3.93	0.54
600	14.2	4.32	0.49
700	15.4	4.69	0.45
800	16.5	5.03	0.42
894	17.5	5.33	0.39
960	18.2	5.54	0.38
1000	18.6	5.66	0.37
1500	23.0	7.02	0.30
1700	24.6	7.51	0.28
1800	25.4	7.74	0.27
1880	26.0	7.93	0.27
2000	26.9	8.20	0.26
2170	28.1	8.57	0.25
2200	28.3	8.63	0.24
2300	29.0	8.84	0.24
2400	29.7	9.05	0.23
2500	30.4	9.25	0.23
2700	31.7	9.65	0.22
3000	33.5	10.2	0.21
4000	39.3	12.0	0.18
6000	49.4	15.0	0.14

[1] The attenuation can be approximated by the formula:

$$\alpha(f[\text{MHz}]) = A \cdot \sqrt{f[\text{MHz}]} + B \cdot f[\text{MHz}] \quad (\text{dB}/100\text{m})$$

A = 0.552
B = 0.0011

[2] Nominal values

[3] Ambient temperature = 40°C (104°F); temperature of inner conductor = 100°C (212°F);
VSWR = 1.0; no solar loading