



RFFT-36SM-001-60M

Bend Insensitive Singlemode Fiber DLC to DLC 36-Fiber Cable Assembly with pulling grip, 60 m

Product Classification

Portfolio	CommScope®
Product Series	RFFT
Product Type	Wireless Fiber Cable Assemblies
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

General Specifications

Ordering Note	CommScope® non-standard product
---------------	---------------------------------

Construction Materials

Fiber Type	G.657.A2
Total Fibers, quantity	36
Jacket Color	Black

Dimensions

Cord Length	60.00 m 196.85 ft
Cable Weight	91.0 kg/km
Diameter Over Jacket	10.28 mm 0.40 in

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
-----------------------	--------------------------------------

General Specifications

Construction Type	Discrete fiber trunk
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface Feature, connector A	Uniboot
Interface Feature, connector B	Uniboot
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius, conductor	10.3 cm 4.0 in
Minimum Bend Radius, furcation	30.0 mm 1.2 in

Optical Performance

Assembly Insertion Loss, typical	0.50 dB
Assembly Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm

Regulatory Compliance/Certifications

Agency	Classification
--------	----------------

RFFT-36SM-001-60M

RoHS 2011/65/EU
ISO 9001:2008

Compliant
Designed, manufactured and/or distributed under this quality management system



* Footnotes

Assembly Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)