Miniature Click-on Hanger for 6–8 mm cable

Product Classification

Product Type Hanger kit

Dimensions

Nominal Size 1/4 in

 Compatible Diameter, maximum
 8.128 mm | 0.320 in

 Compatible Diameter, minimum
 5.842 mm | 0.230 in

 Height
 38.00 mm | 1.50 in

 Length
 35.00 mm | 1.38 in

 Width
 16.00 mm | 0.63 in

Electrical Specifications

DTF Effect 0.1 dB
Return Loss Effect 0.1 dB

Environmental Specifications

Operating Temperature $-40 \, ^{\circ}\text{C} \text{ to } +85 \, ^{\circ}\text{C} \, (-40 \, ^{\circ}\text{F to } +185 \, ^{\circ}\text{F})$

General Specifications

Hanger Type Click-on hanger

Cables per Hanger 2
Color Black

Material Type Engineered plastic

Maximum Stack Height 3

Ordering Note CommScope® non-standard product

Package Quantity 10

Mechanical Specifications

Mounting M8 through hole

page 1 of 2 June 12, 2019



68MCLICK

UV Resistance, minimum with no degradation =100 hours exposure in accelerated UV life chamber

Vibration Survival =4 hours at resonant frequency

Environmental Strength Capability Double cable weight

Packed Dimensions

 Height
 30.4 cm | 12.0 in

 Length
 2.5 cm | 1.0 in

 Shipping Weight
 0.09 kg | 0.20 lb

 Width
 27.9 cm | 11.0 in

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

