



PIM free isolator for SnapStak cable hangers

- Snap in between hanger and mounting surface, and between stacked hangers to remove metal to metal contact and the potential for Passive Intermodulation (PIM).
- For patents see www.cs-pat.com

Product Classification

Product Type	Adapter
Product Brand	PIM-guard
Ordering Note	CommScope® standard product in the United States and Canada

General Specifications

Adapter Type	Snap-in Isolator
Color	Black
Mounting	3/4 in through hole

Dimensions

Height	26.924 mm 1.06 in
Width	43.942 mm 1.73 in
Length	0.043 m 0.14 ft

Material Specifications

Material Type	Engineered plastic
---------------	--------------------

Mechanical Specifications

Maximum Loading	Double stack for hangers SSH-M, SSH-L, SSH-XL
Vibration Survival	=4 hours at resonant frequency

Environmental Specifications

Environmental Strength Capability	Double cable weight
UV Resistance, minimum with no degradation	=1000 hours

SA-ISO

Packaging and Weights

Height, packed	17 cm 6.693 in
Width, packed	13 cm 5.118 in
Length, packed	10 cm 3.937 in
Packaging quantity	10
Weight, gross	0.15 kg 0.331 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

