

RF DC Block Protector, 2.00 – 6.00 GHz, Type N F-F, 10W, IP67

DCB-WFI-NFF



• DCB-WFI-NFF

N Female Connectors on Surge and Protected Side

The DCB series surge arrester is a RF broadband device designed for surge and lightning protection applications where DC Block is required. A DC Blocking device with its internal series capacitor circuit. This DCB unit offers excellent surge / lightning suppression for telecommunications systems.

The DCB series demonstrates excellent RF characteristics while offering outstanding surge protection.

FEATURES:

- Broad Band Design
- Excellent Insertion Loss and Return Loss Characteristics Over Frequency Range
- DC Block
- Multi-Strike Capability
- Max Surge Current of 20kA
- Max Power 10W
- RoHS & CE Compliant
- Bulkhead Mounting (Hex Nut, Lock Washer and O-Ring Included)
- IP67 Rated

APPLICATIONS:

- Wi-Fi
- 4G/5G Cellular Systems
- Other Wireless Applications that Require DC Block to Equipment

RF Specifications

Impedance	50 Ω
Frequency	2.00 – 6.00 GHz
VSWR/Return Loss (Over Frequency)	≤ 1.25 Max / 19.1 dB
Insertion Loss (Over Frequency)	≤ 0.2 dB Max.
Maximum RF Power	10 Watts

Transient Specifications

Protection Circuit	DC Block
Surge Current	IEC 61000-4-5 8/20 μ s Waveform
Maximum Surge	20 kA (1x)
Multi-Strike	10 kA Multiple (10x)
Let-Through Energy	≤ 10 μ J $\pm 20\%$ @ 20kA 8/20 μ s Waveform
Let-Through Voltage	≤ 10 VDC $\pm 20\%$ @20kA 8/20 μ s Waveform

RF DC Block Protector, 2.00 – 6.00 GHz, Type N F-F, 10W, IP67

Mechanical / Environmental Specifications		Material & Finish Specifications		
Storage / Operational Temp	-50°C to +85°C	Component	Material	Finish
Ingress Protection	IP67 IEC 60529	Outer Parts	Aluminum	Ball Burnish
Bellcore	TA-NWT-000487	Connectors	Brass	Tri-Metal
Weight	5.2 oz (147.4 g)	Coupling Nut & Washer	SST	---
RoHS Compliant	Yes	Center Contact	Be Cu / Brass	Gold
CE	Yes	Insulator	PTFE	---

Mechanical Outlines

