

Double Click-on Hanger for 1/2 in coaxial cable

Product Classification

Product Type Hanger kit

Dimensions

Nominal Size 1/2 in

 Compatible Diameter, maximum
 16.256 mm | 0.640 in

 Compatible Diameter, minimum
 15.240 mm | 0.600 in

 Height
 51.00 mm | 2.01 in

 Length
 89.00 mm | 3.50 in

 Width
 45.00 mm | 1.77 in

Electrical Specifications

DTF Effect0.1 dBReturn Loss Effect0.1 dB

Environmental Specifications

Operating Temperature $-40 \, ^{\circ}\text{C}$ to $+85 \, ^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to $+185 \, ^{\circ}\text{F}$)

General Specifications

Hanger Type Click-on hanger

Cables per Hanger 2
Color Black

Material Type Engineered plastic

Maximum Stack Height 3

Ordering Note CommScope® standard product in the United States and Canada

Package Quantity 10

Mechanical Specifications

Mounting Mounting hole clearance for 3/8, 16 UNC or M10 threaded rod

UV Resistance, minimum with no degradation =100 hours exposure in accelerated UV life chamber

Vibration Survival =4 hours at resonant frequency

page 1 of 2 June 27, 2019



L4CLICK

Environmental Strength CapabilityDouble cable weight

Packed Dimensions

 Height
 19.0 cm | 7.5 in

 Length
 17.0 cm | 6.7 in

 Shipping Weight
 0.26 kg | 0.57 lb

 Width
 8.0 cm | 3.1 in

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power