



## FJ-2SM-015-5M

**Ruggedized, Bend Insensitive Singlemode Fiber, DLC to DLC Fiber Distribution Cable, 5 m**

### Product Classification

Portfolio	CommScope®
Product Series	FJ
Product Type	Wireless Fiber Cable Assemblies
Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America

### General Specifications

Ordering Note	CommScope® non-standard product
---------------	---------------------------------

### Construction Materials

Fiber Type	G.657.A2
Total Fibers, quantity	2
Jacket Color	Black

### Dimensions

Cord Length	5.00 m   16.40 ft
Cable Weight	24.9 kg/km
Diameter Over Jacket	6.00 mm   0.24 in

### Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
-----------------------	--------------------------------------

### General Specifications

Construction Type	Discrete fiber tail
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface Feature, connector A	Standard
Interface Feature, connector B	Standard
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius, conductor	6.0 cm   2.4 in
Minimum Bend Radius, furcation	30.0 mm   1.2 in

### Optical Performance

Assembly Insertion Loss, typical	0.50 dB
Assembly Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm

### Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

FJ-2SM-015-5M



## \* Footnotes

Assembly Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)