

**43211A****Butterfly Hanger for 1/2 in or 3/8 in coaxial cable and elliptical waveguide 180, 220, and 240**

Dimensions

Nominal Size	1/2 in
Compatible Diameter, maximum	16.256 mm 0.640 in
Compatible Diameter, minimum	10.414 mm 0.410 in
Height	31.75 mm 1.25 in
Length	40.64 mm 1.60 in
Width	38.10 mm 1.50 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

General Specifications

Hanger Type	Standard butterfly hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Ordering Note	CommScope® standard product in Mexico, Central America, and South America CommScope® standard product in the United States and Canada
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degradation	=500 hours in salt spray chamber
Mounting	3/8 in (M10) drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	=4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

Packed Dimensions

Height	14.8 cm 5.8 in
Length	9.0 cm 3.5 in
Shipping Weight	0.34 kg 0.75 lb
Width	10.6 cm 4.2 in

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
China RoHS SJ/T 11364-2006	Below Maximum Concentration Value (MCV)

43211A

ISO 9001:2008

Designed, manufactured and/or distributed under this quality management system

