



Miniature Click-on Hanger for 9–12 mm cable

Product Classification

Product Type Hanger kit

Dimensions

| | |
|-------------------------------------|----------------------|
| Nominal Size | 1/4 in 3/8 in |
| Compatible Diameter, maximum | 11.989 mm 0.472 in |
| Compatible Diameter, minimum | 8.992 mm 0.354 in |
| Height | 38.00 mm 1.50 in |
| Length | 43.00 mm 1.69 in |
| Width | 20.00 mm 0.79 in |

Electrical Specifications

| | |
|---------------------------|--------|
| DTF Effect | 0.1 dB |
| Return Loss Effect | 0.1 dB |

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

General Specifications

| | |
|-----------------------------|---|
| Hanger Type | Click-on hanger |
| Cables per Hanger | 2 |
| Color | Black |
| Material Type | Engineered plastic |
| Maximum Stack Height | 3 |
| Ordering Note | CommScope® standard product in Mexico, Central America, and South America |
| Package Quantity | 10 |

Mechanical Specifications

| | |
|---|--|
| Mounting | M8 through hole |
| UV Resistance, minimum with no degradation | =100 hours exposure in accelerated UV life chamber |

912MCLICK

Vibration Survival =4 hours at resonant frequency
Environmental Strength Capability Double cable weight

Packed Dimensions

Height 15.2 cm | 6.0 in
Length 2.5 cm | 1.0 in
Shipping Weight 0.13 kg | 0.29 lb
Width 20.3 cm | 8.0 in

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power