

# SSH-1416

---



SnapTak PIM-guard Adjustable Hanger, Version 1.1. Fits 14.1 mm to 16.0 mm Cables – PIM Free Polymer Construction. No Grommets Required.

## Product Classification

<b>Product Type</b>	Hanger kit
<b>Product Brand</b>	SnapTak PIM-guard
<b>Ordering Note</b>	CommScope® standard product in Asia Pacific   CommScope® standard product in Mexico, Central America, and South America   CommScope® standard product in the United States and Canada

## General Specifications

<b>Accessories</b>	Hangers
<b>Cables per Hanger</b>	1
<b>Color</b>	Black
<b>Hanger Type</b>	Snap-in hanger
<b>Mounting</b>	3/4 in drilled cable ladder

## Dimensions

<b>Height</b>	32.258 mm   1.27 in
<b>Maximum Stack Height</b>	3
<b>Maximum Stack Height, Coaxial</b>	3
<b>Width</b>	31.496 mm   1.24 in
<b>Length</b>	31.496 mm   1.24 in
<b>Compatible Diameter, maximum</b>	16.002 mm   0.63 in
<b>Compatible Diameter, minimum</b>	14.097 mm   0.555 in

## Electrical Specifications

<b>Return Loss Effect</b>	0.1 dB
<b>DTF Effect</b>	0.1 dB

# SSH-1416

---

## Material Specifications

**Material Type** Engineered plastic

## Mechanical Specifications

**Vibration Survival** =4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

**Environmental Strength Capability** Double cable weight

**UV Resistance, minimum with no degradation** =1000 hours exposure in accelerated UV life chamber

## Packaging and Weights

**Height, packed** 3.1 cm | 1.22 in

**Width, packed** 20.3 cm | 7.992 in

**Length, packed** 25.4 cm | 10 in

**Packaging quantity** 10

**Weight, gross** 0.54 kg | 1.19 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant



## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power