


Universe	Operators
Туре	Verticality
Category	Pulleys
Subcategory	Carabiner pulleys




# **ROLLCLIP Z**

ROLLCLIP Z is a pulley-carabiner with a gate opening on the non-pulley side to facilitate installation on anchors and devices. It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.



The ROLLCLIP Z pulley may be used as a directional point on the upper attachment point of the ASCENSION handled rope clamp, for short rope ascents. Gate opening on the non-pulley side facilitates installation on the ASCENSION.



The ROLLCLIP Z pulley can be used for tree care to attach the ZIGZAG descender to the attachment bridge on the SEQUOIA harness, for improved lateral mobility.

#### **Short Description** Pulley-carabiner that facilitates installation on anchors and devices

### **Selling Points**

- · Easier handling:
- sheave mounted on sealed ball bearings for excellent efficiency
- gate opening on the non-pulley side, to facilitate installation on devices
- Keylock system prevents any accidental snagging of the carabiner when putting the pulley in place
- H cross-section of carabiner:
- ensures an improved strength-to-weight ratio
- protects markings from abrasion
- Two locking systems available:
- TRIACT-LOCK: automatic locking with triple-action gate opening
- SCREW-LOCK: the manual screw-lock with red band provides a visual warning when the carabiner is unlocked

#### Specification

- Material(s): aluminum
- Min. rope diameter: 7mm
- Max. rope diameter: 13mm
- Sheave diameter: 18mm
- Maximum working load: 2 x 2 = 4kN
- Efficiency: 85%
- Major axis strength: 20kN
- Minor axis strength: 8kN
- Open gate strength: 7kN

## Specifications by reference

Reference(s)	P75 TL	P75 SL
Locking system	TRIACT-LOCK	SCREW-LOCK
Weight	110 g	105 g
Certification(s)	CE EN 362, EN 12278, EAC	CE EN 362, EN 12278, EAC
Gate opening	20 mm	21 mm
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	1
Case quantity	10	10
EAN	3342540815872	3342540815865