

## SELECTED CORD & CABLE DIAMETERS

Type of Cord	AWG Size of Conductors	Number of Conductors-Approximate O.D. in Inches		
		2 Conductor	3 Conductor	4 Conductor
SVO, SVTO	18	.235	.255	—
SJ, SJO, SJT, SJTO	18	.290	.320	.335
	16	.320	.340	.385
	14	.350	.375	.415
	12	.430	.445	.500
	10	.560	.600	.680
S, SO, ST, STO	18	.345	.365	.390
	16	.370	.390	.415
	14	.500	.530	.570
	12	.575	.600	.650
	10	.625	.660	.710
	8	.675	.725	.780
	6	.795	.865	.900
	4	.900	.975	1.100
W	2	1.105	1.170	1.290
	6	.930	1.010	1.100
	4	1.080	1.170	1.270
	3	1.170	1.240	1.340
	2	1.270	1.340	1.480
	1	1.440	1.510	1.680
	1/0	1.520	1.650	1.790
	2/0	1.650	1.750	1.930
	3/0	1.770	1.890	2.070
	4/0	1.920	2.040	2.260
BUS DROP CABLE	250	—	2.390	—
	14	—	.400	—
	12	—	.440	—
	10	—	.500	—
	8	—	.665	—
	6	—	.815	—
	4	—	.955	—
	2	—	1.175	—