

# Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 03-Apr-2025

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name: SC-200 Product Code: 2200

Recommended Use: Cleaning agent

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone

Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

# 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Skin corrosion/irritation Category 1 Sub-category B

Serious eye damage/eye irritation: Category 1 Corrosive to metals Category 1

Label elements

Signal word: Danger

Symbols:

Hazard statements: Causes severe skin burns and eye damage

Precautionary Statements - Do not breathe dust/fume/gas/mist/vapors/spray

Prevention: Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/clothing and eye/face protection

Keep only in original packaging

**Precautionary Statements -**

Immediately call a POISON CENTER or doctor

Response: Eves:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower]. Wash contaminated clothing before reuse.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Precautionary Statements - Storage: Store locked up. Store in corrosion resistant container with a resistant inner liner.

**Precautionary Statements -**

Disposal:

Dispose of contents and container in accordance with local, state and federal regulations.

Hazards not otherwise classified

(HNOC):

Not applicable

Other hazards:

- Corrosive
- · May be harmful if swallowed
- · Harmful contact may not cause immediate pain.
- Harmful if absorbed through skin.
- Inhalation of vapors or mist may cause respiratory irritation.
- Take off and destroy contaminated shoes.
- · Keep out of reach of children
- NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Water	7732-18-5	60-80
Butoxydiglycol	112-34-5	1-5
C9-11 Alcohols Ethoxylated	68439-46-3	1-5
Sodium Xylenesulfonate	1300-72-7	1-5
Butoxyethanol	111-76-2	1-5
Sodium Hydroxide	1310-73-2	1-5
Tetrasodium EDTA	64-02-8	0.1-1
Sodium Nitrite	7632-00-0	0.1-1
CI 15620	1658-56-6	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

**Eye contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Skin contact: Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash

contaminated clothing before reuse. Discard or destroy contaminated shoes.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Ingestion: Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to physicians: NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion. Use extinguishing agent suitable for type of

surrounding fire.

**Specific Hazards Arising from the** 

Chemical:

 $\label{lem:combustion} \mbox{Dried product is capable of burning. Combustion products are toxic.}$ 

**Hazardous Combustion Products:** May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

**Precautions for Firefighters:** protective gear. Cool fire-exposed containers with water spray.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

**Environmental Precautions:** 

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Methods for cleaning up: Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

# 7. HANDLING AND STORAGE

Advice on safe handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions: Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children. Keep from freezing.

**Incompatible materials** Reactive metals such as aluminum, zinc and tin. Acids.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Occupational Exposure Limits:** 

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Butoxydiglycol	TWA: 10 ppm inhalable fraction	-	-
112-34-5	and vapor		
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) Sk* Sk*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Sodium Hydroxide 1310-73-2	Ceiling: 2 mg/m <sup>3</sup>	TWA: 2 mg/m³ (vacated) Ceiling: 2 mg/m³	IDLH: 10 mg/m <sup>3</sup> Ceilina: 2 ma/m <sup>3</sup>

**Engineering Controls:** Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear splash goggles. For severe use-conditions, wear a face shield over the goggles.

**Skin and body protection:** Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other

protective equipment should be considered in order to prevent or minimize contact with this

product.

**Respiratory protection:** Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a

NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General hygiene considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid Color: Red

Odor: Mild glycol ether odor Odor Threshold: No information available

Property Values Remarks • Method

pH: 13.3-14.0

Melting Point / Freezing Point:

No data available

Boiling Point / Boiling Range:

100 °C / 212 °F

Flash Point:  $> 100 \, ^{\circ}\text{C} \, / \, 212 \, ^{\circ}\text{F}$  ASTM D56

Evaporation Rate: < 1 (BuAc = 1)

Flammability (solid, gas): No data available No information available Flammability Limits in Air: No information available

Upper Flammability Limit:

Lower Flammability Limit:

No data available

No data available

Vapor Pressure:No data availableNo information availableVapor Density:No data availableNo information available

Relative Density: 1.063

Solubility(ies): Soluble in water

Partition Coefficient: No data available No information available

Autoignition Temperature: Not applicable Decomposition Temperature: Not applicable

Kinematic Viscosity: No information available

Particle characteristics: Not applicable

# 10. STABILITY AND REACTIVITY

No information available

**Reactivity:** This material is considered to be non-reactive under normal conditions of use.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Not expected to occur with normal handling and storage.

**Conditions to Avoid:** Extremes of temperature and direct sunlight **Incompatible materials:** Strong oxidizing agents. Strong acids.

Hazardous decomposition products: May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

# 11. TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

Eye contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

**Skin contact:** Pain, redness, blistering and possible chemical burn.

Inhalation: Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and

coughing.

Ingestion: Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target organ effects: Blood. Central nervous system. Eyes. hematopoietic system. Kidney. Liver. Respiratory

system. Skin.

Acute toxicity

Numerical measures of toxicity:

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4,907.40 mg/kg
ATEmix (dermal) 9,360.70 mg/kg
ATEmix (inhalation-vapor) 44.10 mg/l
ATEmix (inhalation-dust/mist) 30.41 mg/l

**Component Information:** 

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Water	> 90 mL/kg (Rat)	-	-
7732-18-5			
Butoxydiglycol	= 5660 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
112-34-5			
C9-11 Alcohols Ethoxylated	= 1400 mg/kg (Rat)	-	-
68439-46-3			
Sodium Xylenesulfonate	> 16.2 g/kg (Rat)	> 2000 mg/kg (Rabbit)	-
1300-72-7			
Butoxyethanol	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h

Revision Date: 03-Apr-2025 2200 - SC-200

111-76-2			= 486 ppm (Rat) 4 h
Sodium Hydroxide 1310-73-2	= 325 mg/kg (Rat)	= 1350 mg/kg ( Rabbit )	-
Tetrasodium EDTA 64-02-8	= 1658 mg/kg (Rat)	-	-
Sodium Nitrite 7632-00-0	= 85 mg/kg (Rat)	-	= 5.5 mg/L (Rat)4 h

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** 

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Butoxydiglycol	EC50: >100mg/L (96h,	LC50: =1300mg/L (96h,	-	EC50: >100mg/L (48h,
112-34-5	Desmodesmus	Lepomis macrochirus)		Daphnia magna)
	subspicatus)			
Butoxyethanol	-	LC50: =1490mg/L (96h,	-	EC50: >1000mg/L (48h,
111-76-2		Lepomis macrochirus)		Daphnia magna)
		LC50: =2950mg/L (96h,		,
		Lepomis macrochirus)		
Sodium Hydroxide	-	LC50: =45.4mg/L (96h,	-	-
1310-73-2		Oncorhynchus mykiss)		
Tetrasodium EDTA	-	LC50: =41mg/L (96h,	-	-
64-02-8		Lepomis macrochirus)		
		LC50: =59.8mg/L (96h,		
		Pimephales promelas)		
Sodium Nitrite	-	LC50: =0.19mg/L (96h,	-	-
7632-00-0		Oncorhynchus mykiss)		
		LC50: 0.092 - 0.13mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 0.4 - 0.6mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: 0.65 - 1mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: =2.3mg/L (96h,		
		Pimephales promelas)		
		LC50: =20mg/L (96h,		
		Pimephales promelas)		

Persistence and Degradability: No information available. No information available. Bioaccumulation:

Mobility in Soil: No information available Other adverse effects: No information available.

# 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local regulations. Waste from residues/unused products:

Dispose of in accordance with federal, state and local regulations. Contaminated packaging:

# 14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1760

**Proper Shipping Name:** Corrosive liquids, n.o.s., (contains sodium hydroxide)

Hazard Class: 8
Packing Group: |

Reportable Quantity (RQ): For totes add: RQ, I.B.C.

**Special Provisions:** Shipping descriptions may vary based on mode of transport, quantities, package size,

and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN number or ID number: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide)

Hazard Class: 8
Packing Group: ||

Reportable Quantity (RQ): For totes add: RQ, I.B.C.

#### 15. REGULATORY INFORMATION

### **TSCA** (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### **SARA 313**

This product does not contain listed substances above the "de minimus" level

#### Butoxydiglycol - 112-34-5

applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or SulfonateChemical Category N230

#### Butoxvethanol - 111-76-2

applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or SulfonateChemical Category N230

#### SARA 311/312 Hazard Categories

Acute health hazard:

Chronic Health Hazard:

Fire hazard:

Sudden release of pressure hazard:

No
Reactive Hazard:

No

#### **California Proposition 65**

This product is not subject to warning requirements under California Proposition 65.

# **16. OTHER INFORMATION**

NFPA Health hazards: 3 Flammability: 0 Instability: 0 Special hazards: -

HMIS Health hazards: 3\* Flammability: 0 Physical hazards: 0

Revision Date: 03-Apr-2025

**Revision Note:** Section, 3, 7, 9, 11, 12

#### **Disclaimer:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Page 6 / 6